

# ROCKCRETER 45

## SMALLEST WORKING GUNITE MACHINE

## ROCKCRETER 45



### TECHNICAL SPECIFICATIONS - ROCKCRETER 45

#### DIMENSIONS

- Length - 900mm
- Width - 600mm
- Height - 900mm
- Weight - 200kg
- Output - Up to 4 tons/hr =  $\pm 2m^3$

#### CONVEYING DISTANCE

- Horizontally up to 200m
- Vertically up to 100m

#### AIR REQUIREMENTS

- 4 - 6 bar. @ 240cfm - Electric drive
- 4 - 6 bar. @ 450cfm - Air drive

#### OPTIONS

- Variable speed (380V only)
- Trolley mount
- Drive - 220V / 380V / 525V / Air motor

#### APPLICATIONS

- Refractory Linings
- Furnace Repairs
- Vent Walls
- Bridge Repairs
- Low Volume Guniting
- Rock and Water Features

P.O. Box 18924 Sunward Park 1470 • Log Road, Roodekop, Alberton, South Africa • Tel: +27 11 865 3019/59/71 • Fax: +27 11 865 1346

Company Reg. No: 1947/24677/07

email: [information@rockcrete.co.za](mailto:information@rockcrete.co.za) • website: [www.rockcrete.co.za](http://www.rockcrete.co.za)

As part of our policy of constant product development and improvement, information and specifications contained in this document are liable to change

