

# ROCKCRETER 95

## HIGH OUTPUT DRY GUNITE MACHINE



## ROCKCRETER 95

### FEATURES

- High output
- Mobile
- Robust

### TECHNICAL SPECIFICATIONS - ROCKCRETER 95

#### DIMENSIONS

- Length - 1300mm
- Height - 1100mm
- Output - Up to 6cu.mtrs/hr, dry mix
- Width - 700mm
- Weight - 420-650kg

#### CONVEYING DISTANCE

- Horizontally up to 100m
- Vertically up to 50m

#### AIR REQUIREMENTS

- 4 - 6 bar. @ 600cfm for air drive,
- 365cfm for electric or petrol drive

#### OPTIONS

- Air motor drive - 10hp
- Electric drive - 4 kw. 380V / 525V
- Variable speed electric drive 380V
- Honda petrol drive
- Vibrating hopper

#### APPLICATIONS

- Concrete Repairs
- Spill Ways
- Slope Stabilization
- Vent Seals
- Shaft & Pipe Lining
- Tunnel Support
- Lateral Support
- Dams

P.O. Box 18924 Sunward Park 1470 • Log Road, Roodekop, Alberton, South Africa • Tel: +27 11 865 3019/59/71 • Fax: +27 11 865 1346

Company Reg. No: 1947/24677/07

email: [information@rockcrete.co.za](mailto:information@rockcrete.co.za) • website: [www.rockcrete.co.za](http://www.rockcrete.co.za)

As part of our policy of constant product development and improvement, information and specifications contained in this document are liable to change

